MT-1/NT9 Ultimate All-in-one



The MT-1/NT9 is the ultimate all-in-one portable meter tester with advanced features such as VARh testing, kW demand test, THD consumer line monitoring and bidirectional testing for Net Metering installations. No other equipment needed. The test socket weighs only 6.4 lb!

A fast and accurate test is done within a few minutes! No setup wiring necessary. It is an ideal tool for field testing and periodic sampling and can also be used instead of a test board in the metershop.

The MT-1/NT9 can test commercial and industrial 3-phase meter forms 6S, 8S, 9S, 12S, 14S, 15S and 16S along with residential meter forms 1S, 2S, 3S, 4S and 12S(N).

The MT-1/NT9 comes with a complete calibration report certifying accuracy for both Wh and VARh scales over the entire operating range using a reference standard traceable to NIST.

Full-featured tester at a budget-friendly price!

SPECIFICATIONS

COMPATIBLE METERS	
Single-Phase	1S, 2S, 3S*, 4S, 12S(N)
Three-Phase	6S, 8S, 9S, 12S, 14S, 15S, 16S
Class	10, 20, 100, 200, 320
TEST SOCKET	
Input Voltage	100 - 600VAC
Line Frequency	58 - 62Hz
Power Consumption	75VA (maximum)
Circuit Breakers	2 x 1A (press to reset mechanism)
CURRENT SYNTHESIZERS	
Adjustable Current	0.25 to 50A
Phase Angle (Wh)	Unity and 60° Lag
Phase Angle (VARh)	90° and 30° Lag
3-PHASE WATTHOUR STANDARD	
Typical Accuracy	±0.02%
Guaranteed Accuracy	±0.05%
TEMPERATURE	
Operation	-4° to 140°F (-20° to 60°C)
Storage	-4° to 140°F (-20° to 60°C)
PHYSICAL DIMENSIONS (HxLxD)	
Test Socket (Diam. x D)	6.9" × 7.7"
Remote Control	8.3" × 3.9" × 1"
Carrying Bag	11" x 11" x 8"
WEIGHT	
Test Socket	6.4 lb
Remote Control	0.6 lb
Overall with Carrying Bag	9.1 lb
WARRANTY	
Parts and Labor	1-year limited

*An adapter may be required for some 3S form meters.





1-866-626-1126 info@probewell.com **PROBEWELL.COM**

ACCESSORIES





Focus Adapter

Ouick Release Latch

NTData One software and USB device











Magnetic Adapter